

Tact switches 6×6

INT-1102J Series 6×6mm, Surface mount type



- ▶ **Features** : Broad of stem length & Suitable for variety of controls
- ▶ **Applications** : Operating switches for all kinds of electronic equipments
- ▶ **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.25+0.2/-0.1

▶ Part list

Part No.		Length (mm)	Operating force		Life	QTY per pack (Tape & reel)
			A	B		
INT-1102J43A	INT-1102J43B	4.3	160±50gf	250±50gf	100,000 Cycles Min.	1K (1.2K)
INT-1102J50A	INT-1102J50B	5.0				
INT-1102J60A	INT-1102J60B	6.0				
INT-1102J65A	INT-1102J65B	6.5				750
INT-1102J70A	INT-1102J70B	7.0				
INT-1102J73A	INT-1102J73B	7.3				
INT-1102J75A	INT-1102J75B	7.5				
INT-1102J80A	INT-1102J80B	8.0				700
INT-1102J85A	INT-1102J85B	8.5				
INT-1102J90A	INT-1102J90B	9.0				
INT-1102J95A	INT-1102J95B	9.5				600
INT-1102J11A	INT-1102J11B	11.0				
INT-1102J115A	INT-1102J115B	11.5				
INT-1102J12A	INT-1102J12B	12.0				
INT-1102J125A	INT-1102J125B	12.5				400
INT-1102J13A	INT-1102J13B	13.0				
INT-1102J135A	INT-1102J135B	13.5				
INT-1102J145A	INT-1102J145B	14.5	350			
INT-1102J162A	INT-1102J162B	16.2				
INT-1102J17A	INT-1102J17B	17.0				

* Long life (1KK cycles) is available and part numbers in long life change to INT-1102J43AL ~ INT-1102J135AL.

▶ Drawing

Top view dimensions: 6.0±0.1 (width), 6.0±0.1 (height), 4.5 (pin offset), 4-0.7 (pin length).

Side view dimensions: 0.5 MAX (height), 1±0.3 (height), 5.0 (PCB CENTER), 6.8±0.2 (width), 3.5 (height), L±0.2 (height).

Detail view dimensions: 4-0.7 (width), 4.5 (width).

Circuit diagram

PCB Dimension

Dimensions: 5.9, 3.1, 2.5, 7.5.