

# Tact switches 6×6

**INT-1102S Series** 6×6mm, Surface mount type



- ▶ **Features** : Suitable for high-density mounting
- ▶ **Applications** : Operating switches for all kinds of electronic equipments
- ▶ **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.25+0.2/-0.1

## ▶ Part list

Part No.				Length (mm)	Operating force		Pitch (mm)		Life	QTY per pack	
					A	B	P	Q		(Tape & reel)	(Tube)
INT-1102S43AP	INT-1102S43BP	INT-1102S43AQ	INT-1102S43BQ	4.3	160±50gf	250±50gf	9.0	10.2	100,000 Cycles Min.	1K (1.2K)	90
INT-1102S50AP	INT-1102S50BP	INT-1102S50AQ	INT-1102S50BQ	5.0							
INT-1102S60AP	INT-1102S60BP	INT-1102S60AQ	INT-1102S60BQ	6.0							
INT-1102S65AP	INT-1102S65BP	INT-1102S65AQ	INT-1102S65BQ	6.5							
INT-1102S70AP	INT-1102S70BP	INT-1102S70AQ	INT-1102S70BQ	7.0							
INT-1102S73AP	INT-1102S73BP	INT-1102S73AQ	INT-1102S73BQ	7.3							
INT-1102S75AP	INT-1102S75BP	INT-1102S75AQ	INT-1102S75BQ	7.5							
INT-1102S80AP	INT-1102S80BP	INT-1102S80AQ	INT-1102S80BQ	8.0							
INT-1102S85AP	INT-1102S85BP	INT-1102S85AQ	INT-1102S85BQ	8.5							
INT-1102S90AP	INT-1102S90BP	INT-1102S90AQ	INT-1102S90BQ	9.0							
INT-1102S95AP	INT-1102S95BP	INT-1102S95AQ	INT-1102S95BQ	9.5							
INT-1102S11AP	INT-1102S11BP	INT-1102S11AQ	INT-1102S11BQ	11.0							
INT-1102S115AP	INT-1102S115BP	INT-1102S115AQ	INT-1102S115BQ	11.5							
INT-1102S12AP	INT-1102S12BP	INT-1102S12AQ	INT-1102S12BQ	12.0							
INT-1102S125AP	INT-1102S125BP	INT-1102S125AQ	INT-1102S125BQ	12.5							
INT-1102S13AP	INT-1102S13BP	INT-1102S13AQ	INT-1102S13BQ	13.0							
INT-1102S135AP	INT-1102S135BP	INT-1102S135AQ	INT-1102S135BQ	13.5							
INT-1102S145AP	INT-1102S145BP	INT-1102S145AQ	INT-1102S145BQ	14.5							
INT-1102S162AP	INT-1102S162BP	INT-1102S162AQ	INT-1102S162BQ	16.2							
INT-1102S17AP	INT-1102S17BP	INT-1102S17AQ	INT-1102S17BQ	17.0							

\* Long life (1KK cycles) is available and part numbers in long life change to INT-1102S43APL ~ INT-1102S17APL.

## ▶ Drawing

