

# Low Profile SMT Tact switches

**INT-1187SB Series** 5.1×5.1mm with 1.5mm length, Brass stem, Dustproof, Surface mount type



- **Features** : Low profile & Compact design
- **Applications** : Consumer electronics, Computer devices, Home appliances, Audio-visual equipments
- **Specifications** :

|                    |             |
|--------------------|-------------|
| Rating             | DC 12V 50mA |
| Contact resistance | 100mΩ Max.  |
| Travel (mm)        | 0.25±0.1    |

## ► Part list

| Part No.      | Stem material     | Length (mm) | Operating force | Life                | QTY per pack (Tape & reel) |
|---------------|-------------------|-------------|-----------------|---------------------|----------------------------|
| INT-1187SB15A | Brass             | 1.5         | 200±50gf        | 100,000 Cycles Min. | 4K                         |
| INT-1187SB20A |                   | 2.0         |                 |                     | 3.5K                       |
| INT-1187SB31A |                   | 3.1         |                 |                     | 2.5K                       |
| INT-1187SB43A |                   | 4.3         |                 |                     | 2K                         |
| INT-1187SB15B | Brass             | 1.5         | 250±70gf        |                     | 4K                         |
| INT-1187SB20B |                   | 2.0         |                 |                     | 3.5K                       |
| INT-1187SB31B |                   | 3.1         |                 |                     | 2.5K                       |
| INT-1187SB43B |                   | 4.3         |                 |                     | 2K                         |
| INT-1187SB16A | Brass + Ni plated | 1.65        | 200±50gf        | 4K                  |                            |
| INT-1187SB16B |                   |             | 250±70gf        |                     |                            |

## ► Drawing

